

DECLARATION OF PERFORMANCE

DOP 91751

1. Unique identification code of the product-type

SPC FLOORING

2. Intended use:

Type: SPC

Composition: PVC resin 20-23%, Stone powder 70-75%, Stabilizer 1-2%

Thickness: 3.2-8.0mm, Mass per unit: $6.55-16.5 \text{ kg.m}^{-2}$

Test samples: A) 3.2mm/ 6.55 kg.m^{-2}

B) 8.0mm/ 16.5 kg.m^{-2}

Samples were carried out by manufacturer. Manufacturer declares no fire retardants or a limiting organic material were used.

3. Manufacturer:

HONGKONG RUOTIAN INTERNATIONAL COMPANY LIMITED
UNIT 1101, 11 TH FLOOR, CHAO'S BUILDING, 143-145 BONHAM STRAND EAST,
SHEUNG WAN, HONGKONG.

4. Authorized representative:

Not applicable

5. AVCP - SYSTEM 3

6. Harmonised standard:

Notified body/ies: TEXTILNÍ ZKUŠEBNÍ ÚSTAV, s.p.

Address: Cejl 480/12, Zábřovice, 602 00 Brno, Czech Republic

7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Bfl-s1	EN 14041:2004
Formaldehyde emission	Class E1	EN 14041:2004
Slip resistance	DS	EN 14041:2004

8. Appropriate Technical Documentation

EN 14041:2004/AC:2006

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: 

At place: Changzhou

On date of issue: 2025/08/01

香港若夫国际有限公司
HONGKONG RUOTIAN INTERNATIONAL COMPANY LIMITED
张小玲